

ARclad® IS-8026

Silicone Transfer Adhesive



PRODUCT DESCRIPTION

ARclad® IS-8026 is a silicone transfer film adhesive between two polyester film release liners designed for use in very high temperature and very low temperature applications with excellent long term stability.

FEATURES

- High performance silicone adhesive
- Polyester release liner

BENEFITS

- Outstanding high/low temperature performance
- Tear resistant liner
- Excellent die cutting characteristics

PRODUCT APPLICATIONS

Suggested for flexible circuits, gaskets and heaters where a thin bond line is required. Users should test the product to ensure it meets the specific needs of their application(s). Adhesives Research can tailor the product to meet the needs of specific applications as requested by customers.

PRODUCT CONSTRUCTION – TYPICAL VALUES

Adhesive: 1.0 mils
Liners: 4.0 mils (2)
Total: 5.0 mils nominal

Test Methods

PSTC-133, ASTM D-1000, ART #2060

PRODUCT DIAGRAM



ADHESIVE PROPERTIES – TYPICAL VALUES

180° Peel Adhesion / 2 mil polyester support /
12 in./min. 5 min./SS 40 oz./in.

Test Methods

PSTC-101, ASTM D-3330, ART #1005

ARclad® IS-8026

Silicone Transfer Adhesive



STATIC SHEAR

Temperature	Area	Load	Minutes to Failure
72°F	½" x ½"	500 g.	>72 hrs.

Test Methods:
PSTC-107, ART #1011

STORAGE AND SHELF LIFE

One year from date of manufacture, preferably stored at 55°F (13°C) or below, 50% R.H. Product stored at room temperature for a long period of time may run a risk of liner confusion.

SERVICE TEMPERATURE RANGES

Recommended Minimum Application Temperature:	50°F (10°C)
Maximum Operating Temperature:	500°F (260°C)
Minimum Operating Temperature:	-100°F (-73°C)

(Revised – 03/30/12)

APPLICATION AND STORAGE OF PRESSURE-SENSITIVE ADHESIVE TAPES

Pressure-sensitive adhesive tapes function as a mechanical product; however, the adhesive itself is a chemical composition that can be sensitive to environmental conditions. A purchaser of pressure-sensitive adhesive products should be aware of the shelf life of each product and not purchase more than it can use before the expiration date. Shipping and storage conditions affect shelf life. The optimum storage temperature is 70°F (21°C). Cool, dry storage is recommended.

For best results...

- 1) The surfaces you wish to bond should be clean and free of oil, moisture and dust. If the surface temperature is below 40°F, it may be difficult to achieve a proper bond.
- 2) Do not use a pressure-sensitive adhesive product where it will be exposed to temperatures lower or higher than those designated for each product. Heat can destroy the effectiveness of the bond and extreme cold can cause the adhesive to harden and not adhere properly.
- 3) When the tape is applied, use firm hand or lamination pressure to achieve contact between the adhesive and the surface to which it is applied. Hand rollers or nip rollers may be needed for certain products or applications.

Consult your Adhesives Research sales representative if you need additional information.

WARRANTY AND DISCLAIMER

AR expressly warrants to Purchaser that its product, under normal and intended use, maintenance and storage, is free from defects in workmanship for twelve (12) months from the date of shipment, unless otherwise stated. THIS WARRANTY IS GIVEN IN LIEU OF ALL OTHER WARRANTIES. **AR MAKES NO WARRANTY AS TO EXPERIMENTAL AND DEVELOPMENTAL SAMPLES OR MATERIALS. AR MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** No provisions, statements, diagrams, drawings or pictures contained in any product literature, price list, catalogue, purchase order, product data sheet, order acknowledgment, invoice, delivery ticket, or any other communication by AR, including information on AR's website or statements made by AR's employees or agents, constitute express warranties. Results of tests and recommendations included in communications of AR do not constitute express warranties. MANY FACTORS MAY AFFECT THE USE AND PERFORMANCE OF AN AR PRODUCT IN A PARTICULAR APPLICATION, INCLUDING, AMONG OTHERS, THE PRODUCT SELECTED FOR USE, THE CONDITIONS IN WHICH THE PRODUCT IS USED, THE TIME AND ENVIRONMENTAL CONDITIONS IN WHICH THE PRODUCT IS EXPECTED TO PERFORM, THE MATERIALS TO BE USED WITH THE PRODUCT, THE SURFACE PREPARATION OF THOSE MATERIALS, AND THE APPLICATION METHOD FOR THE PRODUCT; THEREFORE, PURCHASER ACCEPTS RESPONSIBILITY FOR DETERMINING WHETHER AR'S PRODUCT IS FIT FOR A PARTICULAR PURPOSE AND SUITABLE FOR PURCHASER'S METHOD OF APPLICATION. AR retains the right to modify or change its products if in AR's judgment it is advisable.

Purchaser's exclusive remedy and AR's sole obligation for any breach of warranty is limited to, at AR's option, either: 1) replacement of AR's product, or 2) reimbursement of the purchase price of AR's product. **AR DISCLAIMS ANY OTHER OBLIGATION OR LIABILITIES ARISING OUT OF BREACH OF WARRANTY.** AR will not be liable of any loss, damage, expense or consequential, incidental or special damages of any kind.

ARclad® is a registered trademark of Adhesives Research, Inc. Adhesives Research® is a registered service mark of Adhesives Research, Inc. for engineering and design services in the field of pressure-sensitive adhesive systems.

©2014 Adhesives Research, Inc. Printed in USA.

Internet: www.adhesivesresearch.com

Adhesives Research, Inc.
400 Seaks Run Road, P.O. Box 100
Glen Rock, PA 17327
Toll-free: 800-445-6240
Phone: 717-235-7979
Fax: 717-235-8320

Adhesives Research Ireland Ltd.
Raheen Business Park, Limerick, Ireland
Phone: +353 61 300 300
Fax: +353 61 300 700

Adhesives Research Ltd.
United Kingdom
Phone: +44 (0)1371 878187

Adhesives Research Pte. Ltd.
20 Maxwell Road
#10-06 Maxwell House
Singapore 069113
Phone: +65 6774 9580
Fax: +65 6777 7261

Adhesives Research China Co., Ltd.
703B Xin Da Mansion
#322 Xian Xia Road
Shanghai 200335, China
Phone: +86 21 6150 4358
Fax: +86 21 6278 5576